

बिहार राज्य शैक्षणिक आधारभूत संरचना विकास निगम लि०

BIHAR STATE EDUCATIONAL INFRASTRUCTURE DEVELOPMENT CORPORATION LTD.

(A Govt. of Bihar Undertaking)

ISO 9001; 14001; OHSAS 18001

Shiksha Bhawan, Bihar Rashtrabhasha Parishad Campus, Acharya Shivpujan Sahay Path, Saidpur, Patna-800004

Tel. No.: 0612-2660850 • Fax No.: 0612-2660256

E-mail: bseidc@gmail.com • website: http://www.bseidc.in • CIN U80301BR2010SGC015859

दर हेतु अल्पकालीन कोटेशन आमंत्रण सूचना – 02 वर्ष / 2022-23

निबंधित संवेदकों/ख्याति प्राप्त फर्मों/कंपनियों से दिनांक:-29.09.2022 के अपराहन 03:00 बजे तक राज्य के विभिन्न जिलान्तर्गत विभिन्न निर्माण कार्यो में प्रयोग हेतु Furniture Works/ IT Products Works से संबंधित कार्यो हेतु गैर अनुसूचित मदों की आपूर्ति एवं अधिष्ठापन के लिए निम्नांकित मदों हेतु मुहरबंद कोटेशन अधीक्षण अभियंता, बिहार राज्य शैक्षणिक आधारभूत संरचना विकास निगम लि०, पटना के कार्यालय में प्राप्त किया जाएगा एवं उसी दिन अपराहन 03:30 बजे कोटेशनदाताओं या उनके अधिकृत प्रतिनिधियों के समक्ष खोला जाएगा।

Sl. No.	Description of items	Qty	Unit	Rate In Digits	Rate In Words
1	Providing & Fixing of Sublimated plain steel Doors of GP sheet of 1.2 mm thick for frame with 0.8 mm thick for shutter of total thickness 46 mm with 2 nos tower bolt, door stopper, ball bearing, mortish lock and all necessary items with all complete job.(Make Tata pravish, JSW & Jindal)	505.995	SQM		
2	Providing and fixing of Sun Shed for door/window/ ventilator. The Sunshed will be made out ith 0.5 mm PPGI sheet and supported with MS angle bracket. The Sunshed will be 300mm projected from wall . It will be fixed on wall panel with suitable fastenening all complete job as per direction of E/I.	184.2	Mtr.		
3	S/F/F 3 H.P. SUBMERSIBLE PUMP OF ISI MARK WITH STARTER, PANNEL, CABLE, WELL COVER etc. ALL COMPLETE JOB	7	Set		
4	3 core, 10 sq. mm XLPE/PVC insulated PVC sheathed (Heavy duty) armoured electric cable with aluminium conductor	425	RM		
5	Providing, installation, testing and commissioning of UPS, 1 Phase 50 Hz with 60 min back up Ni+Cd battery bank ,Racks, Complete in all respects.				
	1 kVA	2	Each.		
	2 kVA	7	Each.		
	3 kVA	2	Each.		
	5 kVA	1	Each.		
	EXTERNAL LIGHTING				
	LT CABLE & ACCESSORIES				
	LT Cables				

White paper

[Signature]

6	Supply, laying, testing & commissioning of 1.1 kV grade, XLPE insulated, stranded Copper conductor, galvanised steel flat strip / round wire armoured, extruded PVC type ST2 sheathed, heavy duty cable (to be laid on wall surface with necessary clamps / in existing cable trench / cable trays / conduit / pipe sleeves at road crossing or floor as per site requirement) conforming to IS:7098 (Part-1) & IEC:60502 (Part-1), of following sizes:				
	3 Core x 6.0 Sqmm,Al XLPE arm.	3090	RM		
7	Supplying and making one end termination with heavy duty double compression brass gland SIBG type, aluminium lugs duly crimped with crimping tool, PVC tape etc for following size of Armoured PVC insulated & PVC sheathed/ XLPE aluminium conductor cable of 1100 volt grade as required of size.				
	3 X 6 SqmmAl XLPE Cable	244	Each		
	FIRE SYSTEM				
8	Carbon Dioxide type fire extinguisher with cylinder fully charge of 4.0 kg capacity.	87	Each		
	CCTV				
9	Supply / Installation and Commissioning of IR Bullet IP Camera Min 5 MP,1/3" Progressive Scan CMOS ,Min 2688 x 1520 Resolution at 30 fps@30fps ,Min 3.6mm fixed lens (6mm optional),Support H.264 & MJPEG dual codec,Auto/Sunny/Night/Outdoor/Customized, NoiseReduction,Auto(ICR)/Color/B/W,3-Axis adjustment,Max. IR LEDs Length :40m,Day/Night Vision,Min 20fps@4MP,IR Distance Min 30 Meter,,IP-67,	12	Each.		
10	Supply / Installation and Commissioning of IR DOME IP Camera Min 5 MP,1/3" Progressive Scan CMOS ,Min 2688 x 1520 Resolution at 30 fps@30fps ,Min 3.6mm fixed lens (6mm optional),Support H.264 & MJPEG dual codec,Auto/Sunny/Night/Outdoor/Customized, NoiseReduction,Auto(ICR)/Color/B/W,3-Axis adjustment,Max. IR LEDs Length :40m,Day/Night Vision,Min 20fps@4MP,IR Distance Min 30 Meter,,IP-67,	27	Each		
11	SITC of NVR and Software: Recording plus fully functional Application for use with Min16 Channel NVR Recorders and Comptible to IP Cameras. Supports Upto 12 Megapixel IP Cameras and of leading manufacturer,Support various compressions, Including MPEG-4,M-JPEG and H.264,H.265+/H.265, Manufacturer dependant, Graphical Map feature supports realistic camera location, Full Control Hierarchy for simultaneous or Prioritized users.Complete in all respects.	5	Each		
12	LED 55" TV. Complete in all respects with all the accessories required for installation.	5	Each		
13	Wireless Mouse for NVR	5	Each		
14	Min 5 Meter HDMI Cable	5	Each		

Wiley Kumar

B

15	Supply / Installation and Commissioning of 16 Port Network Switch GIGA PoE,IEEE 802.3at and IEEE 802.3af Power over Ethernet (PoE) compliant,24x10/100/1000 Mbps Auto-MDIX PoE ports,Provides up to 30 watts per PoE port,PoE power budget 370W,4 KV surge protection for PoE ports,IEEE 802.3x flow control support,Plug-and-play installation,8.8 Gbps switching fabric,2.75 Mbits RAM Data Buffer,4K MAC address entries,Sturdy metal enclosure	5	Each		
16	Supply / Installation and Commissioning of 8-Port Gigabit Unmanaged Ethernet Switch,8 × Gigabit Ethernet ports.,IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard.,1000 Mbps network access.,Wire-speed forwarding and non-blocking design.,Store-and-forward switching.,Solid high-strength metal shell,Reliable fan-free design,Sturdy metal enclosure	5	Each		
17	Supply / Installation and Commissioning of CAT-6E Cable - 305 Meter Roll	1900	Mtr		
18	Supply and Installation of Cat 6 Patch Cord - 1 Mtrs/2 Mtrs Long as required .	32	Each		
19	Supply / Installation and Commissioning of 6U Switch Rack with 6 point PDU / Fan / Cable Manager / Hardware etc...	5	Each		
20	Termination of Jack Panel, Farulling with Testing and RG-45 Connector	5	LS		
21	Supply Installation Testing & Commissioning of Min 6TB Hard Disk for Video Storage device shall be a Min 15 days Back up .Complete in all respects.	5	Each		
	PROFESSIONAL AUDIO SYSTEM				
22	Supply / Installation and Commissioning of Min 6 Watt Ceilling Mount Speaker	288	Each.		
23	Supply / Installation and Commissioning of Plena Mixer Amplifier,4 microphone / line inputs, plus music source input,Announcement only output, 3 wire volume override ,Wide range of output power (250 Watts), Min 2 tone chime	8	Each.		
24	Supply / Installation and Commissioning of Table Top CondensorMicrophone ,Stylish Table- Top Uni-Directional Condenser Microphone on a Flexible Stem Phantom Powered By Amplifier ,Momentary PTT-Key for Calls, With Priority Contact,Green LED, Indicating Microphone Active Stable Metal Base Design With Fixed 2M Cable And Lockable Din Connector.Seprate Din To XLR Adapter.	8	Each.		
25	Other Connectors (RC Jack / XLR/Wooden cabinet etc...)	8	Each.		
26	Supply and installation of multi colour EPDM Rubber Flooring having thickness of 25 mm for polymeric sports surface to existing surface as per design & drawing, as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I	1817.463	sqm		

Winek Kumar



27	Providing and fixing wooden flooring of make Green/ MIKASA/ VISTA/ Action Tpany's specification (AC4 grade) all complete job as per direction of E/I.	0	sqm		
	PLAY EQUIPMENT				
28	Supplying & Installation of rosewood Carrom board made up of Lacquered Plywood Playing Surface (Side of Square) 73.5 cm to 74 cm, thickness of Playing Surface (Min) 8 mm as per design & drawing, as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I	49	Each		
29	Supply and installation of AB Climber , Type of slide ladder : Full Arch shape Slide ladder made up of virgin grade polyethylene plastic as per design & drawing, as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I	6	Each		
30	Supply and installation of one set of swing of 2 seater 9 ft high (one set of swing of 2 seater 9 ft high)Swing seat made up of Virgin grade polyethylene plastic as per design & drawing, as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I	13	Each		
31	Supply and installation ofOutdoor gym horse rider, Type : Leg Press Single Maximum User Weight (Kg) : 100 kilogram as per design & drawing, as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I	4	Each		
32	Supply and installation of Indoor Fun See Saw having size of Size of see saw (approx)(L x H X base width) (in mm) 1265 x 400 x 400,Size of base of see saw(L x H) (in mm) 400 x 145,Uppertop and bottom width of base of see saw(W x W) (in mm) 60 x 80,Thickness of item(in mm) 2.5,Height of Button mushroom mechanism fitting(in mm) 125 Top and bottom diameter of Button mushroom mechanism fitting(D x D)(in mm) 150 x 40,Size of upper side of Button mushroom mechanism fitting(L x W x D)(in mm) 100 x 35 x 65, Size of middle part of see saw(L x H x W x T)(in mm) 510 x 225 x 55 x 4,Diameter of see saw seat hole(in mm) 7,Space between 7mm and 40mm diameter(in mm) 35,Base Locking(W x H)(in mm) 95 x 70,Size of See saw seat (L x W)(in mm) 540 x 90,Handle(L x Dia x T)(in mm) 260 x 25 x 4 Diameter of align key(in mm) 4 complete as per design & drawing, as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I	10	Each		

Wineet Kumar



FURNITURE					
33	<p>STUDENT BENCH FOR CLASSROOM - Genii 2 seater SM6 - All the panels are made from 11mm thk compact Laminate board with decorative paper on both sides(AS PER IS 2046:1995). The Panles have corners rounded for safty usage. UNDERSTRUCTURE: All side metal frames and cross connectors are ade form combination of 25.4 mm X 1.2 mm thk round ERW Tubes 31.8 x 1.2 mm thk round ERW tubes(As per IS: 7138) which are welded together. The Welded structures and cross connectors are coated with min 45 micron thickness of epoxy polyester coating. Back supprot which are provided at the rear back are made of 50.8 X 25.4 X 1.2 mm thk rectangular ERW tubes (As per IS:7138). The tubes are coated with min. 45 micron thickness of epoxy polyester coating. The storage shelves are made from 0.6 mm thk MS sheet(As per IS:513) fixed below the desktop panel and are coatedwith min 45 micron thickness of epoxy polyester coating. Hooks are provided on the vertical side frames on both sides of the desk for hanging bags/bottles. They are made from 2mm thk MS sheet(As per IS: 513) and are coated with min 45 micron thickness of epoxy polyester coating.The understructure is assembled using M6 trilobular screws(As per DIN 7500) with Zn blue plating(As per IS 1573:1986).Compact Laminate seat and back panels are assembled using M6 countersunk trilobular screws(As per DIN 7500) with Zn black plating(As per IS 1573:1986). Spacers are provided on the top of round tubes for wooden panels fixing. They are made of PP glass filled(30%). Plastic caps made of PP copolymer (3530 grades) are also provided on the rear frame adding more aestheic value to th product. M6 high tensile TVS make bolt(class 8.8) with glass filled nylon level adjustors are provided at the bottom of understructure to take care of unevenness in tfloor with height adjustment of approx 15mm.overall dimation =1240x1130x757 mm</p>	1302	Each		
34	<p>COMPUTER TABLE WITH KEYBOARD TREY - Suppling of study table having dimensions 900mm(L)x 590mm(W) x 745mm(H). The raw material should be used PLB top. PLB having 25mm for table top with 2.0mm thick PVC lipping. Metal parts used is MS ERW Tube, MS CRCA sheets & MS Bright bar. The powder coated should be 35 microns minimum. It should have multi-colored modesty. The mechanism should include self tapping screws and articulated plastic KBPT.</p>	42	Each		

Wine kumar

R

CCTV & SMART CLASSES					
35	<p>Providing, Suupplying ,Instalation and Commisioning of Complete Desktop system along with computer tableProcessor (CPU): Intel Core i5 (sixth generation or newer) or equivalent Operating System: Microsoft Windows 10 Professional x64 (free via Azure Dev Tools for Teaching. Restrictions apply.) Memory: 8 GB RAM Storage: 500 GB internal storage drive Monitor/Display: 14" LCD monitor, resolution of 1600 x 900 or better. Network Adapter: 802.11ac 2.4/5 GHz wireless adapter Other: Internal or external Webcam, lock, carrying case, external hard drive for backup</p>	42	Each		
MISCLENIOUS					
36	<p>Supplying of Yoga Mat/Exercise Mat having size of 180cm (L) X 90cm(W) X 12mm(T), Material- Ethylene Vinyl Acetate of approved colour and texture all complete job as per direction of El.</p>	120	Each		
37	<p>Supplying & Installation of Green Board having size 4 x 8 feet (WidthxHeight) Ceramic Steel Green Dry Erase Writing Boards, frame of material-Anodized extruded Aluminium alloy hollow section of designation 63400 conforming to IS: 1285, surface suitable writting for chalk for colour& black board of approved colour and texture all complete job as per direction of El.</p>	147	Each		
38	<p>Providing & Fixing water purifier cum water cooler made of stainless steel having storage capacity of 40 liter & cooling capacity 40 liter / hour with Reverse osmosis system & ultra violet membrane TDS reduction 90% having automatic back wash system with filtration unit & all other required accessories complete in all respect as per direction of the engineer in charge .</p>	24	Each		
39	<p>Supplying & Installation of Wall Clock made up of Metal Dial And Hands Wall Clocks all complete job as per direction of El.</p>	89	Each		
40	<p>Supplying & Installation of SWAGGERS Buzzer double coil Elecric Bells And Accessories (SWAGGERS) (SW-6 INCH BELL) all complete job as per direction of El.</p>	19	Each		

Wine Kumar

(Handwritten signature)

41	Supplying & Installation of first aid box consists of Clinical Thermometer- Yes,Bandage- Yes,Material of bandage- Cotton,Size of the bandage (L x W)- 3 meter x 5 cm,Adhesive plaster- Yes,Size of Adhesive plaster- 19 x 72 mm,Material of Adhesive plaster- Woven fabric,Sterile gauze swab- Yes,Size of Sterile gauze swab- 5 x 5 cm,Scissor- Yes,Material of the scissor- Stainless steel,Size of scissor- Small,Absorbant cotton roll -Yes,Quantity of absorbant cotton - 250gm,Triangular bandage- Yes,Number of triangular bandage- 2,Antiseptic Liquid- Yes,Type of Antiseptic Liquid- Dettol,Size of antiseptic liquid-50 ml,Antiseptic cream -Yes,Type of Antiseptic cream- Burnol,Quantity of Antiseptic cream-5 gm all complete job as per direction of El.	23	Each		
42	Supplying & Installation of DUSTBIN having capacity of around 100 Litres Dust Bin stand with 2 No. of Compartments. Material- Stainless steel, waste containers or rigid liners,Wheel Lock- Without,Load carrying Capacity (Kgs)- 100,Wall:- Non- Perforated,Lid- hinged,Handle- Without,Wheel- Without,Gripping Provision- Frontal all complete job as per direction of El.	30	Each		
43	Supplying & Installation of Stainless steel DUSTBIN having capacity of 10 Litres all complete job as per direction of El.	118	Each		
44	Providing and supplying of floor matt of size 4 feet x 2.5 feet of juit finish all complete job as per direction of El.	54	Each		
45	Provision of Wall Painting/Sticker (Artistic Work) of requires themes of standard quality selected by E/I with all necessary material, Labour etc. as required all complete job as per direction of El.	962.8	sqm		
46	Supplying, mounting and fixing of LED Signage on exterior wall of size 12'*4' having base of ACP panel board complete with making connections with 1.5 sq mm wire for lumanaries do do all complete job as per direction of E/I. Note- Payment will be given on the basis of per sqm	12	Each		
47	Providing and fixing of brass/Steel/Acrylic Sheet plate of Size 400 mm x 225 mm in height with approved matter all work including fixing and polishing with all carriage and required scaffolding .	107	Each		
48	Providing and fixing of brass/Steel/Acrylic Sheet of plate of Size 300 mm x 100 mm in height with approved matter all work including fixing and polishing with all carriage and required scaffolding .	259	Each		

Wink Kumar

	GYM				
49	<p>Supply and Fixing of Lat Pull Down: Upright structural posts of height 1.90 m is to be schedule HOT DIP Galvanized steel with a 114mm O.D. and 2.2mm (wall) thickness of the tubing. A Pair of Pull down Bars 0.70 m and Dia 38 mm fabricated from 38 O.D. galvanized steel pipes. Bolts, nuts, screws, washers and etc used for assembly shall be stainless steel 304 of tamper resistant stainless steel. Exposed hardware shall be covered with plastic safety caps as per EN16630 standards. The poles are welded on to a base plate made from steel with 114mm inner diameter. Specialized connectors such as clamps and couplings are used to connect the various components of the playground. Joints are Robotic Welded. ALL COMPONENTS MEET WITH EN-16630 SAFETY STANDARDS. EQUIPMENT DIMENSIONS: 1.93 m x 0.75 m x 1.90 m as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I</p>	6	Each		
50	<p>Supply and Fixing of Double Seated Chest Press: Upright structural posts of height 2.20 m is to be schedule HOT DIP Galvanized steel with a 114mm O.D. and 2.2mm (wall) thickness of the tubing. Two pair of U-Shaped Bars of 0.97 m and Dia 48 mm while the handles are placed at a spacing of 642 mm fabricated from 40 O.D. galvanized steel pipes. Bolts, nuts, screws, washers and etc used for assembly shall be stainless steel 304 of tamper resistant stainless steel. Exposed hardware shall be covered with safety caps as per EN16630 standards. The poles are welded on to a base plate made from steel with 114mm inner diameter. Specialized connectors such as clamps and couplings are used to connect the various components of the playground. Joints are Robotic Welded. ALL COMPONENTS MEET WITH EN-16630 SAFETY STANDARDS. EQUIPMENT DIMENSIONS: 1.73 m x 0.75 m x 2.20 m as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I</p>	6	Each		

Wine Kumar

[Signature]

51	<p>Supply and Fixing of Triple Hip Twister: Upright structural posts of height 1.35 m is to be schedule HOT DIP Galvanized steel with a 114mm O.D. and 2.2mm (wall) thickness of the tubing. Circular Handrail Dia 32 mm fabricated from 42 O.D. galvanized steel pipes. Bolts, nuts, screws, washers and etc used for assembly shall be stainless steel 304 grade and shall be of tamper resistant stainless steel. Exposed hardware shall be covered with safety caps as per EN16630 standards. Specialized connectors such as clamps and couplings are used to connect the various components of the playground. Diameter}.All the posts are to be finished with a baked on powder coat finish. Powder coatings used TGIC Polyester powder. ALL COMPONENTS MEET WITH EN-16630 SAFETY STANDARDS. EQUIPMENT DIMENSIONS: Dia 1.6 m x 1.35 m</p>	6	Each		
52	<p>Supply and Fixing of Rider: Upright structural posts of height 1.20 m is to be schedule HOT DIP Galvanized steel with a 114mm O.D. and 2.2mm (wall) thickness of the tubing. Pedals of size 145 mm x 50 mm & Bars 308 mm and Dia 38 mm fabricated from 38 O.D. galvanized steel pipes. Bolts, nuts, screws, washers and etc used for assembly shall be stainless steel 304 of tamper resistant stainless steel. Exposed hardware shall be covered with safety caps as per EN16630 standards. The poles are welded on to a base plate made from steel with 114mm inner diameter. Specialized connectors such as clamps and couplings are used to connect the various components of the playground. Joints are Robotic Welded. ALL COMPONENTS MEET WITH EN-16630 SAFETY STANDARDS.EQUIPMENT DIMENSIONS: 0.97 m x 0.55 m x 1.20 mas per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I</p>	6	Each		
53	<p>Supply and Fixing of Elliptical Cross Trainer: Upright structural posts of height 1.07 m is to be schedule HOT DIP Galvanized steel with a 114mm O.D. and 2.2mm (wall) thickness of the tubing. The Standing Bars 0.93 m and Dia 60 mm fabricated from 60 O.D. galvanized steel pipes. Upper part of Support Handrails of size 0.46 m high and Dia 38 mm fabricated from 38 mm O.D. and 38 mm O.D. galvanized steel pipes. Bolts, nuts, screws, washers and etc used for assembly shall be stainless steel 304 of tamper resistant stainless steel. Exposed hardware shall be covered with safety caps as per EN16630 standards. The poles are welded on to a base plate made from steel with 114mm inner diameter. Specialized connectors such as clamps and couplings are used to connect the various components of the playground. Joints are Robotic Welded. ALL COMPONENTS MEET WITH EN-16630 SAFETY STANDARDS. EQUIPMENT DIMENSIONS: 1.02 m x 0.53 m x 1.52 m</p>	6	Each		


Uttam Kumar

~~12~~

54	Supply and Fixing of Rower: Horizontal bars of length 1.12 m is to be schedule HOT DIP Galvanized steel with a 114mm O.D. and 2.2mm (wall) thickness of the tubing. Handle Bars of 0.88 m and Dia 38 mm fabricated from 40 O.D. galvanized steel pipes. Bolts, nuts, screws, washers and etc used for assembly shall be stainless steel 304 of tamper resistant stainless steel. Exposed hardware shall be covered with safety caps as per EN16630 standards. The poles are welded on to a base plate made from steel with 114mm inner diameter. Joints are Robotic Welded. Powder coatings used is Akzo Nobel's INTERPON POWDER COATING TECHNOLOGY PAINTS. ALL COMPONENTS MEET WITH EN-16630 SAFETY STANDARDS.EQUIPMENT DIMENSIONS: 1.21 m x 0.88 m x 0.78 m as per technical specifications including carriage and necessary required equipment all complete job as per direction of E/I	6	Each	
----	--	---	------	--

विशेष शर्तें—

- कोटेशन दाता सीलबंद लिफाफे में कोटेशन समर्पित कर सकते हैं।
- कोटेशनदाताओं को अपना दर (सभी करों, GST एवं दुलाई व्यय के साथ) अंक एवं अक्षरों में उद्धृत करना होगा। सामग्रियों की आपूर्ति बिहार राज्य शैक्षणिक आधारभूत संरचना विकास निगम (BSEIDC) के अंतर्गत विभिन्न कार्य स्थलों पर किया जाना है।
- कोटेशनदाता द्वारा अपने फर्म का रजिस्ट्रेशन नं०, GST रजिस्ट्रेशन नं० एवं PAN समर्पित करना अनिवार्य है।
- कोटेशन में निहित मदों के लिए संबंधित प्रतिष्ठान/फर्म/आपूर्तिकर्ताओं द्वारा मदवार दर समर्पित किया जाएगा।
- सामग्रियों के इकाई दर के निर्धारण हेतु यह कोटेशन आमंत्रित की गई है। सामग्रियों की आपूर्ति Bulk में ली जाएगी।
- विशेष सूचना के लिए इस कार्यालय का सूचनापट्ट या वेबसाइट www.prdbihar.gov.in एवं इस कार्यालय का वेबसाइट www.bseidc.in पर देखें अथवा अधोहस्ताक्षरी के कार्यालय में कार्यावधि समय 10:00 बजे पूर्वाह्न से अपराह्न 05:00 बजे तक संपर्क किया जा सकता है।


 अधीक्षण अभियंता
 BSEIDC, पटना

✍